

Technical Data Sheet

Guaranteed Values

Brand:

Fluting paper

OnegaFlex

Parameters	Unit of measure	Test method	Substance (g/m ²)							
			42	45	50	60	65	70	80	90
Substance	g/m ²	ISO 536	42±1.5	45±1.5	50±1.5	60±1.5	65±1.5	70±2.5	80±2.5	90±2.5
Moisture	%	ISO 287	8.5 +/-1.5							
SCT _{cd} , min	kN/m	ISO 9895	0.40	0.45	0.50	0.75	0.80	0.90	1.00	1.10
CMT ₃₀ (sample width 15,0 mm), min	N	ISO 7263	-	-	-	55	65	70	90	110
CCT ₃₀ , min	kN/m	GOST 28686	0.20	0.20	0.25	0.35	0.40	0.45	0.50	0.60

Product description:

Fluting paper for production corrugated board and packaging materials.

Information:

Test conditions:
Guaranteed values after conditioning, measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)

Mill`s certificates
• ISO 9001

The timber and recycled materials used in production comply with the basic requirements of NSFC certification. The wood origin verification process complies with the requirements of the Russian chain of custody standard STO NSFC.48861355-004-2023 «National Forest Certification System. Certification Requirements for Chain of Custody Management»